PL1250

DIGITAL PULLER

MAX PULL	MAX SPEED	ROPE DIAMETER
50 kN	5 km/h	16 mm

NEW TESMEC DIGITAL HMI:
7" color display.
Radio remote control.
Data Recorder.

AUTOMATIC REEL WINDER

INTEGRATED COVERS



+ SIMPLE **+ SAFE** **+ RELIABLE**

PERFORMANCE

Max pull	50 kN
Speed at max pull	2 km/h
Max speed	5 km/h
Pull at max speed	17 kN

HYDRAULIC TRANSMISSION

Closed hydraulic with pull pre-setting system that automatically adjust pulling speed.

CHARACTERISTICS

Bull-wheel diameter	400 mm
Bull-wheel material	STEEL
Max rope diameter	16 mm
Weight (without rope)	2500 kg
Number of grooves	7
Suitable for	1 rope
Layout	Single

ENGINE

Diesel	55,4 kW (74 hp)
Cooling system	WATER
Electrical system	12 V

CONFIGURATION

New Tesmec digital HMI.
Automatic reel winder.
Lockable sound proof integrated covers.

Rope clamp for reel change.
Negative self-acting hydraulic brake.
Rigid axle 30 km/h.
Grounding connection point.
Hydraulic front stabilizers.
On board automatic reel winder with level wind, for reel mod. BOF010 and BOF020.
Reel shaft AXR001.

AVAILABLE DEVICES

ALL037	Preheating device up to -30°C.
ALL089	Electronic connection and synchronization between machines.
ALL111	Swivel guide rope roller.
ALL112	Trailer 80 km/h. **EC type-approved for road circulation** with hook Ø 40 mm and lighting system.
ALL261	External printer.
ALL270	Remote Diagnostic system with GPS localization including 3-year subscription.
ALL280	Automatic grease pump.
AXR001	Extra shaft.





7" COLOR DISPLAY



RADIO REMOTE CONTROL

Pictures & drawings can be different according to technical specifications - updating programme variations without notice are possible.

Certified Quality System ISO 9001:2015
Certified Environmental System ISO 14001:2015
Certified Health & Safety System ISO 45001:2018